Reka Glue Guns



Hot-Melt Glue Applicator MS 200



Hot-Melt Glue Applicator Gun MS 200 - Easy Processing of Hot-Melt without compressed air

The MS 200 lets you process hot-melt in form of 43mm sticks, granulate and pillows. The MS 200 does not require compressed air and is thanks to its 600 Watts power consumption ready to go in 5 minutes. The big filling hole makes filling the capacity of 250 ml (8.4 US fluid ounces) comfortable and reduces spillage.

A unique ergonomic shape and an adjustable trigger enable the user to work comfortable and without fatigue. The MS 200 is suited even for delicate hands and both right- and left-handers.

The integrated magnetic foot proves to be a true time saver when putting down and picking up the applicator on magnetic surfaces. A wire-stand provides a secure stand on non-magnetic surfaces.

In combination with a variety of available nozzles the MS 200 serves almost every application conveniently, flexibly and professionally.



Technical Data

MS 200

Article Number 5570, 5571

Weight 1220 g

Power supply 230 V / 50 Hz

Power consumption 600 Watt

Current consumption 2,6 A

Degree of protection I

Class of protection IP 30

Temperature control Thermostat

Temperature limitation Temperature controller

Operating temperature 20 - 200 °C / 70 - 390 °F

Temperature constancy +- 5 °C

Heat-up time appox. 5 min.

Gross tank capacity 250 ml

Conveying system Mechanics

Length of electric cable 1,8 m

Recommended melts Hot-melt granulate, pillows and 43mm (1.7") Sticks



Accessories

Stand for storing

Balancer

Injection needle nozzle

Slot nozzle 18 x 0,5 mm

Pointed nozzle 1,75 x 30 mm

Roundnozzle 1,0 - 1,75 - 2,5 mm

Reka Klebetechnik GmbH & Co. KG

Siemensstr. 6

D-76344 Eggenstein

Telefon: +49 (0)721 970 780 Telefax: +49 (0)721 705 069

E-Mail: in-fo@reka-klebetechnik.de Internet: www.reka-klebetechnik.de